



QUIET CUBE SPECIFICATIONS

Manufactured by Industrial Vacuum Equipment Corporation.

• SKID MOUNTED

4" x 8" rectangular tube frame, fork pockets, and certified lifting cage.

• POWER SOURCE

250 HP electric motor, 460 volt, 3-phase, hostile duty (Full Load amps 282, no load 86)

• SOUND ATTENUATION PACKAGE

Inlet and discharge silencers with sound attenuation enclosure.

• VACUUM AIR FLOW (blower)

Positive displacement 5600 CFM capable of 28" Hg, 5 belt driven, with guard

• FILTRATION SYSTEM

Cyclonic separation. Baghouse - Teflon coated, quick change filter bags with continuous reverse pulse air cleaning. Dual high efficiency blower safety filters.

• INSTRUMENT PANEL (NEMA 4)

Soft start package, push button on/off switch with indicator light, disconnect lever, air pulse on/off switch, material dump on/off switch.

STANDARD EQUIPMENT

- Paint-one color (custom lettering available)
- Wet or dry operation
- Automatic cone vibrator
- Emergency stop button
- 10" inspection manhole
- One year warranty

OPTIONS

- Manual discharge valve
- Auger in hopper (cone)
- Hydraulics (lift cylinder)
- HEPA filtration
- Tool box
- Air compressor - 120 PSI
- Trailer mounted to DOT standards
- 300 HP electric motor




Dimensional Drawing On Reverse Side



Industrial Vacuum Equipment Corporation
N7959 Birch Road • Ixonia WI, 53036
800-331-4832 • 920-261-1136 • FAX 920-261-7117
www.industrialvacuum.com

INDUSTRIAL VACUUM



Quiet Cube 250

The Strong Silent Type.

Raised Height - 183"



Length - 162"

Weight - 16,000 lbs.

Stowed Height - 126"



Width - 100"