

HURRICANE 500_{EM}



Dimensional drawing on other side

HURRICANE 500_{EM} SPECIFICATIONS

•SKID MOUNTED

4" x 8" rectangular tube frame, fork pockets & certified lifting cage

•POWER SOURCE

100 HP electric motor, 460 volt, 3 phase hostile duty motor (full load amps 115)

•SOUND ATTENUATION PACKAGE

12" blower discharge silencer & 12" inlet blower silencer

•VACUUM AIR FLOW (Blower)

Roots Dresser 616 DVJ, 2350 CFM capable of 23" Hg, 5 belt driven with OSHA approved guard.
150 HP option: 2350 CFM capable of 27" Hg



•FILTRATION SYSTEM - 3 STAGE

Cyclonic separation. Baghouse - 37 Teflon coated quick change filter bags with continuous reverse pulse air cleaning. High-efficiency blower safety filter

•INSTRUMENT PANEL (NEMA 4)

Soft start package, push-button on/off switch with indicator light, disconnect lever, filter cleaning on/off switch, material dump on/off switch

STANDARD EQUIPMENT

- Paint - one color (custom lettering available)
- Wet or dry operation
- Automatic cone vibrator
- Emergency stop button with 50' cord

OPTIONS

- 150 HP electric motor
- Slide gate discharge
- 16" manhole on baghouse
- Auger in hopper (cone)
- Hydraulics (lift cylinder)
- HEPA filtration
- Tool box
- Air compressor - 120 PSI
- Trailer mounted to DOT standards



INDUSTRIAL VACUUM EQUIPMENT CORPORATION
N7959 Birch Road • Ixonia, WI 53036
800-331-4832 • 920-261-1136 • FAX 920-261-7117
www.IndustrialVacuum.com



HURRICANE 500EM



DIMENSIONS

WIDTH 76"

WEIGHT 10,000 lbs

