

40 HP Exhaust Blower

(800)331-4832

Sales, Service & Parts



Hurricane 40 HP Exhaust/Ventilation Blower

Specifications:

- **STEEL SKID:** Certified lifting padeyes, 4"x10" fork tubes on four sides
- **BLOWER:** Cincinnati Fan, AMCA B Spark Resistant Construction, SQBI-180, Class III Wheel, High Pressure Backward-Curved, Arr 4 Upblast, 9000 CFM @ 19" w.g., direct drive, housing access door and bottom drain, flanged connections,
- **MOTOR:** 40 HP, 3530 RPM , 480 Volt, 3 phase, 60 Hz, TEFC, severe duty premium efficiency (EXPLOSION PROOF CLASS I GROUP D optional motor)
- **MOTOR CONTROLLER:** NEMA 4X Stainless Steel construction, motor starter with circuit breaker disconnect (pad lockable), START/STOP pushbuttons, operating pilot lights, (NEMA 7 EXPLOSION PROOF CLASS 1 GROUP D optional enclosure)
- **OUTLET SILENCER:** Heavy duty carbon steel construction (interior/exterior), vertical discharge with automatic rain cap, flanged connection, welded seams, wire mesh spacer, Fiberglass cloth and insulation – 80 dBA @ 5 feet
- **INLET FAN ADAPTOR:** flanged connections, welded seams, (2) Flanged 12 inch diameter hose connection collars
- **SOUND ATTENUATION PACKAGE (Optional):** Complete sound attenuating enclosure consisting of vertical foam panels surrounding entire unit – 75 dBA @ 5 feet.

Dimensions-106" tall x 60" wide x 86" long

Weight-3850 lbs

High Quality Finish (Epoxy primer, Acrylic urethane top coat)

Warranty: 3 month labor, 12 month parts

FOB: Ixonia, WI 53036

(Please note that picture shown may reflect different size and options, all specifications and prices are subject to change without notice)

Industrial Vacuum Equipment Corp
N7959 Birch Road, Ixonia, WI 53036
Toll Free (800)331-4832 / Fax (920)261-7117

