



DH/AC 5000 HP

DH/AC 5000 HP

• SKID MOUNTED

Three to four sided fork truck tubes large enough for an 8 ton fork truck.

• STACKABLE

Four point shipyard lifting cage with connections at 65" requiring no steps to connect rigging. Certified lifting eyes with certification printed on unit.

• POWER SOURCE

460 Volt, 3Phase, 15 horsepower direct drive, high output motor with digitized motor savers to protect from power surges.

DH Amp – 125 Max. (normal operation DH & AC 65 amps)

AC Amps - 35

• QUIET OPERATION

Below 83 decibels at 3 meters.

3-in-1 cooling, DH and blower unit

• FAN

5,000 CFM @ 16" W.C.

15 ton A/S. 45KW heat with optional 60 extra KW

STANDARD EQUIPMENT

- Powder coated galvanized steel with Nyalic corrosion resistant coating
- Electronic variable CFM
- 6 Level variable temperature and humidity settings with a flip of a switch
- Camlock electrical connections with S.S. ground stud
- 12" duct connection
- Continuous duty cycle
- 150 Amp circuit breaker
- Low temperature sensor
- One year warranty

Dimensional Drawing On Reverse Side



Industrial Vacuum Equipment Corporation
N7959 Birch Road • Ixonia WI, 53036
800-331-4832 • 920-261-1136 • FAX 920-261-7117
www.industrialvacuum.com



DH/LAC 5000^{HP}

Height - 67"



Weight - 3,000 lbs.

Length - 96"

Width - 91"