

800-331-4832
920-261-1136
Fax 920-261-7117



N7959 Birch Road
Ixonia, WI 53036
www.industrialvacuum.com

Hurricane DH/AC 5000 Dehumidifier/Air Conditioner



SPECIFICATIONS

- ❖ DH Amp – 88 Max (normal operation DH & AC 40 amps)
- ❖ AC Amp – 25
- ❖ 460 Volt, 3 Phase, 15 horsepower, high output motor with digitized motor savers to protect from power surges
- ❖ 15 HP Variable speed, direct drive fan
- ❖ 16 " WC (water column)
- ❖ 12.5 ton
- ❖ Dimensions: 59" High x 71" Wide x 99" Long
- ❖ Weight: 2600 lbs
- ❖ Stackable four point shipyard lifting cage with connections at 63" requiring no steps to connect rigging
- ❖ Three side fork truck tubes large enough for an 8 ton fork truck
- ❖ 18" duct connections (2)
- ❖ Quiet operation below 84 decibels at 1 meter
- ❖ Camlock electrical connections with S.S. ground stud
- ❖ Certified lifting eyes with certification printed on unit
- ❖ Powder coated galvanized steel with a Nyalic corrosion resistant coating
- ❖ Electronic variable CFM
- ❖ 6 Level variable temperature and humidity settings with a flip of a switch

SPECIFICATIONS (continued):

- ❖ Continuous duty cycle
- ❖ 3-in-1 cooling, DH and blower unit
- ❖ 125 Amp circuit breaker
- ❖ Low temperature sensor
- ❖ Warranty: 90 day Parts & Labor. 12 months Parts only