

800-331-4832  
920-261-1136  
Fax 920-261-7117



N7959 Birch Road  
Ixonia, WI 53036  
www.industrialvacuum.com

## **ELECTRIC 1000 SHIPYARD COMPRESSOR**



### **Technical Information:**

Capacity—990 cfm @ 125 PSIG  
Maximum Operating Pressure—135 PSIG  
Weight—8,000 lbs – with Air Dryer 12,500 lbs  
Outlet Size—3” NPT  
Dimensions—Facing control panel\*  
(L\* x W x H) - 140” x 75” x 86”  
Package Amp Draw Table—  
460/3/60—269.5 Amps  
575/3/60—215.7 Amps  
Sound Level—80 dBA  
200HP Electric Motor

### **Air Cooled Data:**

Aftercooler CTD—15° F  
Fan Air Flow—15,000 cfm

### **Standard Equipment:**

- 2 Stage Rotary Screw Air Compressor
- Nema 4 Electrical Enclosure
- 460V Open Drip Proof High Efficiency Motor
- Star-Delta Starter / Soft Start
- Aircooled Aftercooler
- Intellisys Controller / With Weather Guard
- Phase Monitor / Voltage Monitor
- High Efficiency Coalescing Filter
- Coalescing / Particulate Filter
- 4 Way 6” x 9” Fork Truck Tubes
- 4 Point Certified Lifting / Military Spec
- Shipyards Lift Cage
- 1700 Series Camlock Electric Connections
- Instrument Quality Air

### **Options:**

- On Board Desiccant Air Dryer (Shown)  
\*Changes Length to 184”