

HURRICANE 350S



Dimensional drawing on other side

SPECIFICATIONS

•SKID MOUNT

Heavy duty steel frame with fork pockets and adjustable jack stands

•POWER SOURCE (Electric or Diesel)

50HP TEFC electric motor, NEMA 4X enclosure with all controls and disconnect
50HP Kubota Diesel Engine

•VACUUM AIR FLOW (Blower)

Positive displacement, 1250 CFM @ 14"Hg vacuum, 3 belt driven

•FILTRATION SYSTEM (3-Stage)

Stage 1: Cyclonic separation

Stage 2: Baghouse, 12 Teflon coated, sealed-edge, quick-change cartridges with continuous reverse pulse cleaning system

Stage 3: Blower Safety Filter

SAFETY FEATURES

- OSHA approved belt guard
- Optional HEPA filtration
- Blower safety filter
- Emergency stop button

STANDARD EQUIPMENT

- Paint - one color (custom lettering optional)
- Wet or dry operation
- Hydraulic jack to raise/lower baghouse
- (4) jack stands
- Inspection door (Hopper)
- Manual vacuum break
- Gravity style dump door

OPTIONS

- Certified lift cage
- HEPA filtration
- Air compressor
- Auto dump
- Reverse pulse filter cleaning
- Trailer mounted



INDUSTRIAL VACUUM EQUIPMENT CORPORATION
N8150 Maple Street • Ixonia, WI 53036
800-331-4832 • 920-261-1136 • FAX 920-261-7117
www.IndustrialVacuum.com



HURRICANE 350S



DIMENSIONS

WIDTH 69"

WEIGHT 4,000 lbs

Raised Height 147"

Stowed Height 104"



Discharge Height 59"

Length 141" (with dump counterbalance)