

HURRICANE 500_{EM}

HURRICANE 500_{EM} SPECIFICATIONS

- SKID MOUNTED

4"x 8" rectangular tube frame, fork pockets & certified lifting cage

- POWER SOURCE

100 HP electric motor, 460 volt, 3 phase hostile duty motor (full load amps 115)

- SOUND ATTENUATION PACKAGE

12" blower discharge silencer & 12" inlet blower silencer

- VACUUM AIR FLOW (Blower)

Roots Dresser 616 DVJ, 2350 CFM capable of 23" Hg, 5 belt driven with OSHA approved guard.
150 HP option: 2350 CFM capable of 27" Hg



Dimensional drawing on other side



- FILTRATION SYSTEM - 3 STAGE

Cyclonic separation. Baghouse - 37 Teflon coated quick change filter bags with continuous reverse pulse air cleaning. High-efficiency blower safety filter

- INSTRUMENT PANEL (NEMA 4)

Soft start package, push-button on/off switch with indicator light, disconnect lever, filter cleaning on/off switch, material dump on/off switch

STANDARD EQUIPMENT

- Paint - one color (custom lettering available)
- Wet or dry operation
- Automatic cone vibrator
- Emergency stop button with 50' cord

OPTIONS

- | | |
|-----------------------------|---------------------------|
| •150 HP electric motor | •HEPA filtration |
| •Slide gate discharge | •Tool box |
| •16" manhole on baghouse | •Air compressor - 120 PSI |
| •Auger in hopper (cone) | •Trailer mounted to |
| •Hydraulics (lift cylinder) | DOT standards |



INDUSTRIAL VACUUM EQUIPMENT CORPORATION
N8150 Maple Street • Ixonia, WI 53036
800-331-4832 • 920-261-1136 • FAX 920-261-7117
www.IndustrialVacuum.com



HURRICANE 500_{EM}



DIMENSIONS

WIDTH 96"

WEIGHT 10,000 lbs

