HURRICANE 755

SPECIFICATIONS

Dimensional drawing on other side

•TRAILER MOUNTED Chassis - tandem 8,000# axles, 4"x 6" rectangular tube frame, with four 8-lug P225/R-16 ten ply steel belted radials. DOT lighting with electric brakes. Trailer light wiring harness, with 7-pin connector

•POWER SOURCE John Deere Tier 4 turbo-charged diesel engine, 6.8L. 225 HP @ 2,200 RPM

•P.T.O. (clutch) Double disc, 11.5" with iron plates

•VACUUM AIR FLOW (blower) Roots Dresser 3660 CFM capable of 28" Hg, direct drive through flex coupling, with easy access guard

•FILTRATION SYSTEM (3-Stage)
Stage 1: Cyclonic separation
Stage 2: Baghouse/37 Teflon coated, quick change filter bags with continuous reverse pulse air cleaning
Stage 3: Dual high efficiency blower safety filters with dirty filter shut-down system

•HYDRAULICS 4.5 GPM, 2200 PSI, direct drive

•ENCLOSURE Lockable steel shroud over all major components

•INSTRUMENT PANEL (Fully enclosed) 12 volt key start, safety system (low oil pressure/high water temperature auto shutdown) Digital: oil pressure, water temperature, ammeter, RPM, hour meter. Filter cleaning on/off switch, material vacuum & dump time controls, air compressor psi gauge

•AIR COMPRESSOR Direct drive Bendix twin cylinder; water cooled & oil pressure fed. Haldex air dryer with electronic heater. AMSE certified air tank mounted on vibration isolators (provides air to pneumatic controls and self cleaning filter sytem)

STANDARD EQUIPMENT

- Paint - one color (custom lettering available)
- Wet or dry operation
- Tool box
- Automatic cone vibrator
- 100 gallon fuel tank
- Adjustable pintle hook
- Remote Emergency stop button
- Dual front hydraulic lift legs to level trailer
- Spare tire & carrier
- Hinged dome on baghouse

OPTIONS

- Cold weather package
- HEPA filtration
- Slide gate discharge
- Hazardous waste package
- Auger in hopper (cone)
- Auxiliary air hose 120 PSI
- Skid mount
- 200 HP electric motor
- 4 point certified lifting cage
- High reach package
- Gooseneck trailer
- High reach package for discharge up to 11 ft

SAFETY FEATURES

- OSHA approved drive guard
- Remote emergency stop button
- Safety struts for baghouse
- Emergency trailer breakaway chain
- Wheel chocks
- Optional HEPA filtration
- Electric brakes
- Low oil or high temp engine shutdown

INDUSTRIAL VACUUM

INDUSTRIAL VACUUM EQUIPMENT CORPORATION
N8150 Maple Street • Ixonia, WI 53036
800-331-4832 • 920-261-1136 • FAX 920-261-7117
www.IndustrialVacuum.com

INDUSTRIAL VACUUM

HURRICANE

HURRICANE 755

DIMENSIONS

WIDTH 99″

WEIGHT 14,880 lbs