



•SKID MOUNTED

 $4^{\prime\prime}x$ 10" rectangular tube 3-way frame, fork pockets and certified lifting cage.

•POWER SOURCE

200 HP electric motor, 480 volt, 3 phase, premium efficiency (Full Load amps 222, no load 86).

•SOUND ATTENUATION PACKAGE

Patented "Quiet Cube" technology. 85 DBA at full vacuum.

•VACUUM AIR FLOW (Blower)

Positive displacement of up to 4500 CFM capable of 27" Hg, 6 belt driven, with guard.

•FILTRATION SYSTEM

Cyclonic separation. Baghouse - Teflon coated quick change filter bags with continuous reverse pulse air cleaning. Dual high efficiency blower safety filters.

•INSTRUMENT PANEL (NEMA 4)

Soft start package, push-button on/off switch with indicator light, disconnect lever, air pulse on/off switch, vacuum on/off switch.

STANDARD EQUIPMENT

- •Tool less flip-top baghouse lid
- •Gravity style dump door
- •Paint one color (custom lettering available)
- •Wet or dry operation
- •Automatic cone vibrator
- •Emergency stop button
- •10" inspection manhole
- •One year warranty

OPTIONS

- •Manual discharge valve
- •Auger in hopper (cone)
- •Hydraulics (lift hopper)
- •HEPA Filtration
- Tool box
- •Air compressor 120 PSI



INDUSTRIAL VACUUM EQUIPMENT CORPORATION N8150 Maple Street • Ixonia, WI 53036 800-331-4832 • 920-261-1136 • FAX 920-261-7117 www.IndustrialVacuum.com

Dimensional drawing on other side

15,000 LBS EMPTY WEIGHT

