

12 MVT TRAILER

Diesel Powered Ventilation Blower

•MOBILE or SKID MOUNTED

Heavy duty 2" X 4" Structural frame

•TRAILER

Single axle, 6,000 lbs. Torflex with electric brakes

•POWER SOURCE

Available in a diesel or electric powered model 24 HP, 1.03 liter, Tier 4 Final Kohler engine

•HIGH CAPACITY

Air flow of 12,000 CFM at 4" WG



STANDARD EQUIPMENT

- Steel construction with single point lift eye, (4) D-ring tie downs
- Pintle style trailer, electric brakes, (2) stabilizing jacks
- DOT approved LED trailer lighting & reflective recognition tape
- Standard one year limited warranty
- (1) 18" diameter QF inlet with safety screen
- (1) 18" diameter QF outlet with safety screen
- Steel engine shroud
- 38 gallon fuel tank- extended run time
- 12 VDC strobe light
- Engine block heater 120 VAC
- · High quality finish- epoxy primer & polyurethane top coat



Dimensional drawing on other side

VERSATILITY - OPTIONS

- · Cummins, John Deere or Kubota Engine
- · Skid base with fork pockets
- 460 volt, 3 phase electric motor
- Hose storage with locking compartment
- Silencer (intake or discharge)
- LED work lights
- Manual Damper (inlet or outlet) Explosion
- proof motor & controls
- 3,500 lbs. Tandem Leaf spring axles
- 20 lbs ABC fire extinguisher
- AMCA type "B" fan construction, aluminum
- Ducting and hose accessories



INDUSTRIAL VACUUM EQUIPMENT CORPORATION N8150 Maple Street • Ixonia, WI 53036 800-331-4832 • 920-261-1136 • FAX 920-261-7117 www.industrialvacuum.com

12 MVT TRAILER

Diesel Powered Ventilation Blower

Industrial Vacuum manufacturers ventilation blower systems
Ranging from 600 CFM - 40,000 CFM, Contact us for more information



DIMENSIONS

Weight 3,300 lbs.



