



# HURRICANE DIESEL VACUUM MODELS



MODEL	300	400	500	600	755	828
Inches of Mercury/CFM	15" / 850	27" / 1450	27" / 2350	16" / 3660	27" / 3660	27" / 5660
Horsepower	30	75	170	170	225	325
Primary filterbags	10	37	37	37	37	37
Secondary filters	Cartridge	Cartridge	Cartridge	Cartridge	Cartridge	Cartridge
Empty weight (lbs)	3,500	8,900	10,900	10,800	13,500	16,700
Dimensions (in)	152Lx113Hx79W	205Lx131Hx99W	204Lx133Hx99W	204Lx133Hx99W	206Lx139Hx99W	254Lx139Hx99W
Recommended hose size	3"/4"	4"	4"	6"	6"	6"/8"
Max Conveying Distance (ft)	100	500	1000	1000	1300	1500
Tons per hour	3-4	7-9	10-12	8-10	15-17	19-21
Gallons per minute	80	200	300	275	350	400
All figures above are based off of proven operators vacuuming sand at approximately <b>100 feet</b> .						

## Industries Served

### INDUSTRIAL CLEANING

SURFACE PREP • STEEL MILLS • FOUNDRIES  
 WASTE WATER • BRICK/REFRACTORY • CEMENT  
 AEROSPACE • WOOD • CHEMICAL CLEAN ROOMS  
 PLASTICS • MILLING • ELECTRONICS

### SANDBLASTING & MEDIA REMOVAL

SHIPBUILDING • SHIPYARD REPAIR  
 RAILROAD CAR CLEANING

### HAZARDOUS MATERIAL REMOVAL

NUCLEAR • ASBESTOS • SPILL RECOVERY  
 SITE REMEDIATION • HAZARDOUS WASTE  
 CONTAMINATED WASTE • BIOLOGICAL WASTE

### WATER, POWER PLANTS & REFINERIES

OIL & GAS • CATALYST REMOVAL  
 CARBON BLOCK • CARBON CHANGE-OUT



Industrial Vacuum Equipment Corp.  
 N8150 Maple St • Ixonia, Wisconsin • 53036  
 (920) 261-1136 • IndustrialVacuum.com