



HURRICANE ELECTRIC VACUUM MODELS



300S



400EM



500EM



QC150



800EM



QC200

MODEL	300S/QC300	400EM	500EM/QC150	800EM/QC200	QC250
Inches of Mercury/CFM	15" / 850	27" / 1400	27" / 2350	27" / 4500	27" / 3660
Horsepower	30	75	150	200	250
Primary filterbags	10	37	37	37	37
Secondary filters	Cartridge	Cartridge	Cartridge	Cartridge	Cartridge
Empty weight (lbs)	2,800/5,000	8,500	10,000	14,500/15,000	16,000
Dimensions (in)	113Lx102Hx69W/ 130Lx113Hx71W	132Lx123Hx96W	129Lx120Hx76W/ 143Lx120Hx102W	189Lx123Hx96W/ 176Lx128Hx102W	162Lx126Hx100W
Recommended hose size	3"/4"	4"	4"	6"	6" or 8"
Max Conveying distance (ft)	100	500	1000	1300	1500
Tons per hour	3-4	7-9	10-12	15-17	19-21
Liquid gallons per minute	80	200	250	300	400

All figures above are based off of proven operators vacuuming sand at approximately 100 feet.

Industries Served

INDUSTRIAL CLEANING

SURFACE PREP • STEEL MILLS • FOUNDRIES
WASTE WATER • BRICK/REFRACTORY • CEMENT
AEROSPACE • WOOD • CHEMICAL CLEAN ROOMS
PLASTICS • MILLING • ELECTRONICS

SANDBLASTING & MEDIA REMOVAL

SHIPBUILDING • SHIPYARD REPAIR
RAILROAD CAR CLEANING

HAZARDOUS MATERIAL REMOVAL

NUCLEAR • ASBESTOS • SPILL RECOVERY
SITE REMEDIATION • HAZARDOUS WASTE
CONTAMINATED WASTE • BIOLOGICAL WASTE

WATER, POWER PLANTS & REFINERIES

OIL & GAS • CATALYST REMOVAL
CARBON BLOCK • CARBON CHANGE-OUT



Industrial Vacuum Equipment Corp.
N8150 Maple St • Ixonia, Wisconsin • 53036
(920) 261-1136 • IndustrialVacuum.com